

DC 1800 DC 2800^{H EX} Stainless Steel



Dustcontrol's DC 1800/2800 EX are valued both for its easy handling and capacity when being used to reduce the risks of potential dust explosions in ATEX zone 22 (non-conductive dust).

However, there are areas with high hygienic demands (e.g. the food processing industry), which surpass the abilities of our standard DC 1800/2800 EX.

Suitable for operation in environments with potentially combustible dust (non-conductive); stainless steel design enables the use of alkaline wash solutions; high resistance to acids.



DC 1800^{EX} Stainless Steel



DC 2800^{EX} Stainless Steel



Supplied with (Part No)

- Suction hose, antistatic 38 ATEX (2027)
- Suction hose ATEX, Ø 38, 5 m/ 20 in (2007)
- Floor nozzle 370 A-38, ESD-certified (7235E)
- Suction pipe Ø38 mm/1.5" (7257)
- Fine filter, polyester (42028)
- HEPA H13 filter (42027)

Part No DC 2800 H EX Stainless Steel

114104	115V, 60 Hz, USA/CAN
114105	230V, 50 Hz, EU



Technical data

Weight	18/19 kg / 40/42 lb
Flow at open inlet, 115V	210 m ³ /h /124 ft ³ /m
Flow at open inlet, 230V	185 m ³ /h /109 ft ³ /m
Neg. Pressure max, 115V	30 kPa
Neg. Pressure max, 230V	25 kPa
Power consumption, 115V	1500 W
Power consumption, 230V	1300 W
Sound level	70 dB(A)